

HEAVY DUTY[®] HOIST RINGS

SAFETY IS OUR ^{only} BUSINESS

BETTER VALUE! UP TO 30% LOWER COST!

** IN STOCK FOR IMMEDIATE DELIVERY **



- Stronger than Machined
- Forged Alloy Steel
- **MINIMUM** 5:1 Rated Load
- Interchangeable with Machined Hoist Rings
- 40% Fewer Parts
- **100%** Mag Inspected
- World's Largest Inventory

**THE ORIGINAL AND ONLY
HEAVY DUTY[®]**

PATENT NO 4570987*,
4641986*, 5405210

SEE BACK FOR DIMENSIONS AND CAPACITIES

American DRILL BUSHING CO.
CBC INDUSTRIES, INC.

www.americandrillbushing.com
Email: ADB@americandrillbushing.com

SALES:

7141 Paramount Blvd
Pico Rivera, CA 90660
Toll Free: 800-423-4425
Fax: 323-725-8740

FACTORY & HEADQUARTERS:

5740 Hunt Road
Valdosta, GA 31606
Phone: 229-253-8928
Fax: 229-253-8929


* Patent expired



For information on larger sizes, including our new
EZ-TORQUE® HOIST RINGS with capacities to 250,000#
 visit www.americandrillbushing.com.

HEAVY DUTY® HOIST RINGS

SPECIFICATION TABLE



Part No.	Rated Load	A	B	C	D	E	F	G	K	L	M	TL* ft/lb.	WT lbs.
33112	550	.65	2.29	.96	.44	.56	3.23	1/4-20	1.25	.15	1.57	5	.50
33212	800	.65	2.29	.96	.44	.56	3.23	5/16-18	1.25	.15	1.51	7	.52
33214	800	.65	2.29	.96	.44	1.06	3.23	5/16-18	1.25	.15	1.51	7	.54
33312	1000	.65	2.29	.96	.44	.56	3.23	3/8-16	1.25	.15	1.45	12	.56
33314	1000	.65	2.29	.96	.44	1.06	3.23	3/8-16	1.25	.15	1.45	12	.58
33316	2250	.65	2.29	.96	.44	1.06	3.23	1/2-13	1.25	.15	1.45	25	.60
33512	2500	1.00	3.50	1.50	.75	.75	5.31	1/2-13	1.89	.17	2.56	28	1.71
• 33513	2500	1.00	3.50	1.50	.75	.75	6.87	1/2-13	1.89	.17	4.12	28	2.04
33515	2500	1.00	3.50	1.50	.75	1.00	5.31	1/2-13	1.89	.17	2.56	28	1.72
• 33505	2500	1.00	3.50	1.50	.75	1.00	6.87	1/2-13	1.89	.17	4.12	28	2.05
33516	2500	1.00	3.50	1.50	.75	1.25	5.31	1/2-13	1.89	.17	2.56	28	1.82
• 33517	2500	1.00	3.50	1.50	.75	1.25	6.87	1/2-13	1.89	.17	4.12	28	2.15
33612	4000	1.00	3.50	1.50	.75	.75	5.31	5/8-11	1.89	.17	2.44	60	1.76
• 33613	4000	1.00	3.50	1.50	.75	.75	6.87	5/8-11	1.89	.17	4	60	2.09
33614	4000	1.00	3.50	1.50	.75	1.00	5.31	5/8-11	1.89	.17	2.44	60	1.78
• 33604	4000	1.00	3.50	1.50	.75	1.00	6.87	5/8-11	1.89	.17	4	60	2.11
33615	4000	1.00	3.50	1.50	.75	1.25	5.31	5/8-11	1.89	.17	2.44	60	1.88
• 33616	4000	1.00	3.50	1.50	.75	1.25	6.87	5/8-11	1.89	.17	4	60	2.21
33714	5000	1.00	3.50	1.50	.75	1.00	5.31	3/4-10	1.89	.17	2.31	100	1.89
• 33715	5000	1.00	3.50	1.50	.75	1.00	6.87	3/4-10	1.89	.17	3.87	100	2.22
33716	5000	1.00	3.50	1.50	.75	1.50	5.31	3/4-10	1.89	.17	2.31	100	2.02
• 33717	5000	1.00	3.50	1.50	.75	1.50	6.87	3/4-10	1.89	.17	3.87	100	2.35
33108	7000	1.40	5.10	2.05	1.00	.95	7.37	3/4-10	2.81	.18	3.57	100	7.20
• 33168	7000	1.40	5.10	2.05	1.00	.95	9.00	3/4-10	2.81	.18	5.20	100	7.93
33102	7000	1.40	5.10	2.05	1.00	1.20	7.37	3/4-10	2.81	.18	3.57	100	7.23
• 33162	7000	1.40	5.10	2.05	1.00	1.20	9.00	3/4-10	2.81	.18	5.20	100	7.96
33103	7000	1.40	5.10	2.05	1.00	1.45	7.37	3/4-10	2.81	.18	3.57	100	7.25
• 33163	7000	1.40	5.10	2.05	1.00	1.45	9.00	3/4-10	2.81	.18	5.20	100	7.98
33104	8000	1.40	5.10	2.05	1.00	.95	7.37	7/8-9	2.81	.18	3.32	160	7.33
• 33164	8000	1.40	5.10	2.05	1.00	.95	9.00	7/8-9	2.81	.18	4.95	160	8.06
33101	8000	1.40	5.10	2.05	1.00	1.20	7.37	7/8-9	2.81	.18	3.32	160	7.33
• 33161	8000	1.40	5.10	2.05	1.00	1.20	9.00	7/8-9	2.81	.18	4.95	160	8.06
33105	10000	1.40	5.10	2.05	1.00	1.45	7.37	1-8	2.81	.18	3.20	230	7.57
• 33165	10000	1.40	5.10	2.05	1.00	1.45	9.00	1-8	2.81	.18	4.82	230	8.30
33106	10000	1.40	5.10	2.05	1.00	1.20	7.37	1-8	2.81	.18	3.20	230	7.63
• 33166	10000	1.40	5.10	2.05	1.00	1.20	9.00	1-8	2.81	.18	4.82	230	8.36
33107	10000	1.40	5.10	2.05	1.00	2.20	7.37	1-8	2.81	.18	3.20	230	7.81
• 33167	10000	1.40	5.10	2.05	1.00	2.20	9.00	1-8	2.81	.18	4.82	230	8.54
33402	15000	2.00	6.75	2.87	1.25	1.88	9.22	1 1/4-7	3.88	.18	3.74	470	15.74
33401	15000	2.00	6.75	2.87	1.25	2.63	9.22	1 1/4-7	3.88	.18	3.74	470	16.0
33420	20000	2.00	6.75	2.87	1.25	2.63	9.22	1 3/8-6	3.88	.32	3.62	670	17.2
33424	24000	2.00	6.75	2.87	1.25	2.63	9.22	1 1/2-6	3.88	.32	3.49	800	18.1
33427	30000	2.00	6.75	2.87	1.25	2.96	9.22	2-4 1/2	3.88	.32	3.49	800	22.9
33432	30000	2.00	6.75	2.87	1.25	2.96	9.22	2-8	3.88	.32	3.49	800	22.9

• Long Bar Models
 * Recommended torque load

For load ranges of 50,000 to 250,000 lbs. refer to our Safety Engineered Hoist Rings. Replacement screws are available.

ALSO AVAILABLE IN METRIC SIZES.

HEAVY DUTY HOIST RINGS ARE COMPLETELY INTERCHANGEABLE WITH S.E.H.R.

© JULY 2006